



> PRINT

**FS-2100D**

A4 BLACK AND WHITE  
PRINTER

# THE POWERFUL PRINTER FOR SMALLER OFFICES



- > Up to 40 A4 pages per minute with up to 1,200 dpi resolution
- > Duplex unit for double-sided printing as standard
- > 100-sheet multi-purpose tray, 500-sheet universal cassette
- > 5 line LCD display for easy navigation and clear messages
- > High capacity of 128 MB RAM as standard for complex documents
- > Convenient printing directly from USB Flash memory
- > Powerful options for enhanced functionality and performance
- > Optional Gigabit or wireless network functionality
- > Exceptionally low printing costs in its class

For smaller teams and for single users this tough, durable and reliable device is the perfect choice. With up to 40 ppm in black and white this device is capable of handling large workloads. Its aesthetic design, great usability and flexibility in paper handling makes it a must for small teams. Due to its long life components, running costs and environmental impact are exceptionally low.



ECOSYS stands for ECOlogy, ECONomy and SYStem-printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly. The modular design concept allows you to add workflowenhancing functions as required. Integrated system software provides long-term crossnetwork compatibility. KYOCERA's long-life components cost you and the environment less.

#### PRESCRIBE IIe

With the KYOCERA page design and control language PRESCRIBE IIe, even complex graphics, logos and forms (multipart forms) can be created independently on the system and saved and updated in the printer. Consequently, integration into print files no longer applies. They are only accessed as required and therefore relieve the load on the network.

#### GENERAL

**Technology:** KYOCERA ECOSYS Laser

**Control panel:** 5 line LCD display with alphanumeric keypad

**Engine speed:** Up to 40 pages per minute in A4

**Resolution:** 1,200 dpi

**Duty cycle:**

Maximum. 150,000 pages per month

Maximum Average. 15,000 pages per month

Average. 4,000 pages per month

**Warm-up time:** Approx. 15 seconds or less from power on

**Time to first page:** Approx. 9 seconds or less

**Dimensions:** (W x D x H): 380 mm x 416 mm x 285 mm

**Weight:** Approx. 13.5 kg (main unit)

**Power source:** 220/240 V, 50/60 Hz

**Power consumption**

Printing: 564 W

Stand-by: 11.5 W

Power-Saving (ECOpower): 3.0 W

Typical Electricity Consumption (TEC): 2.24 kWh/week

**Noise (Sound pressure level: ISO 7779 / ISO 9296):**

Printing: 52.4 dB(A) LpA

Stand-by: 25.9 dB(A) LpA

**Safety standards:** GS, TÜV, CE

This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

#### PAPER HANDLING

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

**Input capacity:** 100-sheet multi-purpose tray; 60–220 g/m<sup>2</sup>; A4, A5, A6, B5, Letter, Legal, Custom (70 x 148 – 216 x 356 mm)  
500-sheet universal paper cassette, 60–120 g/m<sup>2</sup>; A4, A5, B5, Letter, Legal, Custom (140 x 210 – 216 x 356 mm)  
Max. input capacity incl. options: 2,600 sheets

**Duplex unit:** Duplex as standard supports A4, A5, B5, Letter, Legal, Custom (140 x 210 mm – 216 x 356 mm), 60–120 g/m<sup>2</sup>

**Output capacity:** 250-sheet-face-down

#### KYOCERA NetViewer

KYOCERA NetViewer enables complete monitoring and control of all ECOSYS printers and digital KYOCERA multifunction units from any Windows® PC and thus provides ideal network administration. It also supports the standardised SNMP protocol.

#### Command Center RX

The Command Center RX enables to control and manage various settings by accessing the device via Web browser. E.g. automatically updating of screens, customizing user screens, viewing department & restriction settings.

#### USB Host Interface for USB Flash Memory

Documents can be printed directly from a USB Flash Memory (e.g. USB stick) via the USB host interface. The documents stored as PDF, XPS, TIFF or JPEG are selected directly via the printer's control panel. No computer is required.

#### CONTROLLER

**CPU:** PowerPC 465 / 750 MHz

**Memory:** 128 MB RAM, max. 1,152 MB RAM

**Standard interface:** USB 2.0 (Hi-Speed), 2 USB Host Interfaces, Slot for optional internal print server or SSD hard disc, Slot for optional SD/SDHC-Card

**Controller language:** PRESCRIBE IIe

**Emulations:** PCL6 (PCL5c / PCL-XL), PostScript® 3 (KPDL 3), XPS Direct Print\*\*, PDF Direct Print 1.7, IBM Proprinter X24E, Epson LQ-850 with automatic emulation sensing

**Operating systems:** All current Windows operating systems, Mac OS X Version 10.4 or higher, UNIX, LINUX as well as other operating systems on request

**Fonts/Barcodes:** 93 scalable fonts for PCL/PostScript®, 8 fonts for Windows Vista®, 1 Bitmap font, 45 barcodes (e.g. EAN8, EAN13, EAN128) with automatic generation of checksums as well as support of two-dimensional barcodes PDF-417 under PRESCRIBE (PCL and other barcodes available as an option)

**Integrated Accounting:** 100 department codes

#### CONSUMABLES

**TK-3100 Toner-Kit:** Microfine toner for 12,500 pages A4  
Capacity of starter toner is 6,000 pages A4. Average continuous toner yield in accordance with ISO/IEC 19752

#### OPTIONS

**PF-320 Paper feeder (max. 4 units):** Max. 500 sheets; 60–120 g/m<sup>2</sup>; A4, A5, B5, Letter, Legal, Custom (148 x 210 mm – 216 x 356 mm)

**PF-315+ Bulk paper feeder and PB-325 Printer base:** Max. 2,000 sheet, 60–220 g/m<sup>2</sup>, not to be combined with PF-320

**CB-360 Cabinet:** Wooden desk with storage capacity

**Memory upgrade:** MDDR2-512: 512 MB, MDDR2-1024: 1,024 MB

**SD/SDHC\*-Card:** 1 slot (up to 32 GB) for storage of documents incl. Private Print functionality

**HD-6 SSD hard disc:**

32 GB for easy document management

**Data security kit (E):** in line with security level EAL3

**USB IC Card Reader + Card Authentication Kit (B):**

Support for various authentication keys available

**Optional interface**

**IB-50:** Gigabit Ethernet: 10BaseT/100BaseTX/1000BaseT (RJ-45)

**IB-51:** Wireless LAN (802.11b/g/n)

**IB-32:** Parallel IEEE1284 interface kit


#### MODEL VARIATIONS

**FS-2100D/KL3:** FS-2100D incl. warranty extension KYOLife 3 years

#### WARRANTY

2-year warranty\*\*\* as standard. KYOCERA guarantees the drum and developer for 3 years or maximum 300,000 pages (whichever occurs sooner), provided the printer is used and cleaned in accordance with the service instructions.

**KYO LIFE** The up to 5-year on-site warranty extension for printer and options.



KYOCERA Document Solutions (UK) Ltd  
Eldon Court, 75-77 London Road, Reading RG1 5BS  
Tel: 0118 931 1500 – Fax: 0118 931 1108  
www.kyoceradocumentsolutions.co.uk – info@duk.kyocera.com

\* KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

\*\* Requires memory expansion \*\*\* Depending on the country

YOUR KYOCERA BUSINESS-PARTNER

